



9 dB
12cm FAN

- **NEW ULTRA-SILENT TACENS AURA PRO FAN WITH A NEW REDUCED MOTOR AND LONGER BLADES FOR BETTER PERFORMANCE AND LOWER NOISE. INCLUDES THE EXCLUSIVE TACENS FLUXUS PRO BEARING AND ANTIVIBRATION SYSTEM**
- **MANUAL SPEED CONTROL ON PCI FOR TOTAL USER FAN CONTROL FROM ULTRA-SILENT TO POWERFUL SILENT COOLING**
- **POWERFUL FOUR SUPERCONDUCTOR HEATPIPES WITH DIRECT HEATPIPE CPU CONTACT FOR FASTEST HEAT TRANSFER**
- **HEATSINK FINS WITH NATURAL WAVE-SHAPE TECHNOLOGY FOR SMOOTHER AND MORE SILENT AIRFLOW**
- **CHIPSET AND MEMORY COOLING THANKS TO ITS VERTICAL AIRFLOW SYSTEM**
- **LOW WEIGHT**
- **NEW CLIP FOR FASTER AND EASIER INSTALLATION**

**INTEL LGA775
AMD K8
(754, 939 & 940)
AMD AM2
MULTI-CORE
COMPATIBLE**

HEATSINK SPECIFICATIONS

DIMENSIONS (mm)	162(L) x 128(W) x 85(H) mm / MODULE
WEIGHT	350 g
MATERIAL	6Φ x 4 heatpipes direct contact with CPU Aluminum fins (59±1 fins)
SOCKET TYPE	INTEL LGA 775, AMD 754,930 & 940 AND AMD AM2

FAN SPECIFICATIONS

DIMENSIONS (mm)	120 x 120 x 25 mm
WEIGHT	125g (170g WITH PCI FAN CONTROL)
FAN SPEED	800 – 1500 R.P.M.
FAN AIRFLOW	58.53 – 72.24 CFM
LIFE EXPECTANCY	MORE THAN 60000 hrs
BEARING	TACENS FLUXUS PRO BEARING
VOLTAGE RATING	12V
NOISE LEVEL	9 – 16 dB

TACENS FLUXUS PRO

BEARING

ULTRA SILENT

LOWER NOISE THAN SLEEVE OR BALL BEARINGS

DUST PROOF DESIGN

CLOSED CONSTRUCTION PREVENT THE DUST AND FOREIGN BODY INTO DE BEARING

LONG LIFE

MORE THAN 60000 hrs

LOW WORKING TEMPERATURE

THE FAN WORKS PERFECTLY IN VERY HOT CONDITIONS